

LEVO GEN 3



LEVO GEN 3



The all-new Turbo Levo delivers an unimaginable fusion of human and machine. Harness the technology and take your riding beyond belief. More speed. More distance. More freedom. More trails ridden, more pure stoke generated, more unforgettable experiences... experienced. Since its introduction, the Turbo Levo has set the marker every other e-mountain bike aims for, and this new bike raises that bar again. It's the distillation, application and amplification of everything we know about mountain biking—a potent blend of motor assist, chassis,

suspension, and geometry that adds up to an unbelievable trail ride. The seamless integration of our proprietary Turbo Levo motor, battery, and controller can't be found anywhere else, and amplifies your ride by quadrupling the power you bring to the pedals so naturally the bike feels like it's an extension of you, only faster. Turbo Levo is the previously impossible combination of ride quality, range, and robustness. Believe it.





PRODUCT DESCRIPTION

- The Levo’s motor/controller system is a full integration of the bike’s 565-watt motor and 700Wh battery with a radically advanced and seamlessly integrated controller. The result is massive power delivered, up to 20mph/32kph, to get you to the top of your favorite descent with just a quarter of the effort, and much faster, giving even more of the quality ride you yearn for, and more of it than ever before possible.

- Our next-generation TCU2 is your information hub, with customizable display fields, including the exact percentage of battery level, and features our all-new, bar-mounted MicroTune function to adjust power delivery in 10% increments, so you get exactly the support you need to experience precisely the ride you want.

- A dedicated “Mullet” design with a 27.5” wheel in the back and 29” up front delivers a nimble ride that carves circles around other full-power e-MTBs. A generous cockpit centers you on the bike, optimizing traction and corner control. The low bottom bracket, slack headtube angle and reduced fork offset keep things stable in the rough.

- The Levo offers six distinct geometry settings, allowing you to easily hone its performance for any style, any terrain. Head angle can be adjusted between 63- and 65.5-degrees. Bottom bracket height can be fine-tuned up or down by 7mm.

- The Levo’s 150mm of Enduro-inspired travel is supple on small bumps, devours square-edged hits without a twitch, eats massive G-outs for breakfast, yet still offers amazing pedal response and delivers your power to the ground with total efficiency.

- The Levo’s S-Sizing is based on what matters—rider size and style, not inseam. Six sizes, all with similar headtube lengths and standover, allow you to choose the size that best suits your individual style. Smaller S-Size numbers are going to be nimble and more flickable, while bigger S-Sizes deliver more stability and a roomier ride.

GEOMETRY

	S1	S2	S3	S4	S5	S6
STACK (MM)	605	617	626	635	644	653
REACH (MM)	412	432	452	477	502	532
HEADTUBE LENGTH (MM)	105	105	115	125	135	145
HEADTUBE ANGLE (DEGREES)	64.5	64.5	64.5	64.5	64.5	64.5
B!B HEIGHT (MM)	352	350	350	350	350	350
B!B DROP (MM)	25	27	27	27	27	27
TRAIL (MM)	130	130	130	130	130	130
FORK LENGTH (FULL) (MM)	557	567	567	567	567	567
FORK RAKE/OFFSET (MM)	44	44	44	44	44	44
FRONT!CENTER (MM)	738	760	784	814	843	878
CHAIN!STAY LENGTH (MM)	442	442	442	442	442	442
WHEELBASE (MM)	1179	1200	1225	1255	1284	1318
BIKE STAND!OVER HEIGHT (MM)	752	776	783	787	788	790
SEAT!TUBE LENGTH (MM)	380	390	405	425	445	465
SEAT!TUBE ANGLE (DEGREES)	78	77.2	76.7	76.2	76.2	76.2
MAX SEATPOST INSERTION (MM)	210	220	240	255	275	295
MIN SEATPOST INSERTION (MM)	80	80	80	80	80	80
CRANK LENTH (MM)	160	160	160	160	160	160
HANDLEBAR WIDTH (MM)	780	780	780	780	780	780
STEM LENGTH (MM)	40	40	50	50	50	50
SADDLE WIDTH (MM)	155	155	143	143	143	143
SEATPOST LENGTH (MM)	100	125	150	170	170	190

	BLUE GHOST GRAVITY FADE / BLACK / LIGHT SILVER	CARBON / SMOKE / BLACK	METALLIC WHITE SILVER / CHROME / DREAM SILVER	SATIN REDWOOD / SMOKE / BLACK	MAROON / BLACK
COMP NB	!	!	!	!	!
EXPERT NB	!	96421!320	!	!	96421!330
PRO NB	!	!	!	95221!110	!
SW NB	95221!070	!	95221!080	!	!
SW FRAMESET NB	75221!030	!	!	!	!

LEVO S-WORKS



SW SPECS

Specifications subject to change without notice

FRAME	FACT 11m full carbon, 29" front wheel, 27.5" rear wheel, full internal cable routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel, geo adjust head tube, geo adjust horst pivot
SHIFT LEVERS	SRAM Eagle AXS Rocker Paddle
CASSETTE	SRAM XG-1299, 12-speed, 10-52t
CHAIN	SRAM XX1 Eagle, 12-speed
REAR DERAILLEUR	SRAM XX1 Eagle AXS
CRANKSET	Praxis Carbon M30, custom offset, 160mm
CHAINRINGS	SRAM X-Sync Eagle, 104 BCD, 32t, steel
FRONT WHEEL	Traverse SL 29
REAR SHOCK	FOX FLOAT X2 Factory, LSC, LSR, 2-position lever, 55x210mm, Kashima
REAR WHEEL	Traverse SL 27.5
FRONT TIRE	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.6"
INNER TUBES	Standard, Presta Valve
REAR TIRE	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, 27.5x2.6"
SADDLE	Bridge, 155/143mm, Hollow Ti-rails
SEATPOST	RockShox Reverb AXS, 30.9, 1X remote, (S1:100mm, S2: 125mm, S3: 150mm, S4-S6: 170mm)
FORK	FOX FLOAT 38 Factory 29, Grip2 damper, 44mm offset, HSC, LSC, HSR, LSR, 110x15mm, 1.5" tapered steerer, 160mm travel, Kashima
SEAT BINDER	Alloy, 38.6, with ti bolt
BATTERY	Specialized M3-700, Integrated Battery, 700WH, SBC-B22
CHARGER	Custom charger, 42V4A w/ Rosenberger plug
WIRING HARNESS	Custom Specialized wiring harness
SWAT	SWAT CC steerer tube integrated tool with chain tool and link
HANDLEBARS	Specialized Trail, FACT Carbon, 6-degree upsweep, 8-degree backsweep, 27mm rise, 780mm, 35mm
STEM	Deity Copperhead, 35.0mm
GRIPS	Deity, Knuckleduster, Black
FRONT BRAKE	Magura MT7 with custom Loic lever blade, 203mm
REAR BRAKE	Magura MT7 with custom Loic lever blade, 203mm



METALLIC WHITE SILVER / CHROME / DREAM SILVER



BLUE GHOST GRAVITY FADE / BLACK / LIGHT SILVER



LEVO PRO



PRO SPECS

Specifications subject to change without notice

FRAME	FACT 11m full carbon, 29" front wheel, 27.5" rear wheel, full internal cable routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel, geo adjust head tube, geo adjust horst pivot
REAR DERAILLEUR	SRAM X01 Eagle, 12-speed
SHIFT LEVERS	SRAM X01 Eagle trigger, 12-speed, single click
CASSETTE	SRAM XG-1295 Eagle, 10-52t
CHAIN	SRAX X01 Eagle, 12-speed
CRANKSET	Praxis carbon M30, custom offset, 160mm
CHAINRINGS	SRAM X-Sync Eagle, 104 BCD, 32T, Steel
FRONT WHEEL	Traverse Carbon 29
REAR SHOCK	FOX FLOAT X2 Factory, LSC, LSR, 2-position lever, 55x210mm, Kashima
REAR WHEEL	Traverse Carbon 27.5
FRONT TIRE	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.6"
INNER TUBES	Standard, Presta Valve
REAR TIRE	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, 27.5x2.6"
SADDLE	Bridge, 155/143mm, Hollow Ti-rails
SEAT BINDER	Alloy, 38.6
SEATPOST	FOX Transfer, 30.9, S1: 100mm, S2: 125mm, S3: 150mm, S4/S5: 175mm, S6: 200mm
FORK	FOX FLOAT 38 Factory 29, Grip2 damper, 44mm offset, HSC, LSC, HSR, LSR, 110x15mm, 1.5" tapered steerer, 160mm travel, Kashima
BATTERY	Specialized M3-700, Integrated Battery, 700WH, SBC-B22
CHARGER	Custom charger, 42V4A w/ Rosenberger plug
WIRING HARNESS	Custom Specialized wiring harness
SWAT	SWAT CC steerer tube integrated tool with chain tool and link
HANDLEBARS	Specialized Trail, FACT Carbon, 6-degree upsweep, 8-degree backsweep, 27mm rise, 780mm, 35mm
STEM	Deity Copperhead, 35.0mm
GRIPS	Deity, Knuckleduster, Black
FRONT BRAKE	SRAM Code RSC, 4-piston caliper, hydraulic disc, S1-S3: 200mm, S4-S6: 220mm
REAR BRAKE	SRAM Code RSC, 4-piston caliper, hydraulic disc, 200mm



SATIN REDWOOD / SMOKE / BLACK



LEVO EXPERT



EXPERT SPECS

Specifications subject to change without notice

FRAME	FACT 11m full carbon, 29" front wheel, 27.5" rear wheel, full internal cable routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel, geo adjust head tube, geo adjust horst pivot
REAR DERAILLEUR	SRAM X01 Eagle, 12-speed
SHIFT LEVERS	SRAM X01 Eagle trigger, 12-speed, single click
CASSETTE	SRAM XG-1275, 12-speed, 10-52t
CHAIN	SRAM GX Eagle, 12-speed
CRANKSET	Praxis forged M30, custom offset, 160mm
CHAINRINGS	SRAM X-Sync Eagle, 104 BCD, 32T, Steel
FRONT WHEEL	Traverse 29
REAR SHOCK	FOX FLOAT X2 Performance Elite, LSC, LSR, 2-position lever, 55x210mm
REAR WHEEL	Traverse 27.5
FRONT TIRE	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.6"
INNER TUBES	Standard, Presta Valve
REAR TIRE	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, 27.5x2.6"
SEAT BINDER	Alloy, 38.6
SEATPOST	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SLR LE lever, 34.9, S1: 100mm, S2: 125mm, S3: 150mm, S4/S5: 175mm, S6: 200mm
FORK	FOX FLOAT 38 Performance Elite 29, Grip2 damper, 44mm offset, HSC, LSC, HSR, LSR, 110x15mm, 1.5" tapered steerer, 160mm travel
BATTERY	Specialized M3-700, Integrated Battery, 700WH, SBC-B22
CHARGER	Custom charger, 42V4A w/ Rosenberger plug
WIRING HARNESS	Custom Specialized wiring harness
SWAT	SWAT CC steerer tube integrated tool with chain tool and link
STEM	Specialized Trail, 3D-forged alloy, 4-bolt, 6-degree rise
GRIPS	Deity, Knuckleduster, Black
HANDLEBARS	Specialized Trail, 7050 alloy, 8-degree backsweep, 6-degree upsweep, 30mm rise, 780mm, 35mm clamp
SADDLE	Bridge Comp, Hollow Cr-mo rails, 155/143mm
FRONT BRAKE	SRAM Code RS, 4-piston caliper, hydraulic disc, S1-S3: 200mm, S4-S6: 220mm
REAR BRAKE	SRAM Code RS, 4-piston caliper, hydraulic disc, 200mm



MAROON / BLACK



CARBON / SMOKE / BLACK



LEVO FRAMESET



SW FRAMESET SPECS

Specifications subject to change without notice

FRAME	S-Works FACT 11m full carbon, 29 Trail Geometry, Integrated down tube battery, enclosed internal cable, dropper post routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel
CRANKSET	Praxis Carbon M30, custom offset
CHAINRINGS	SRAM X-Sync Eagle, 104 BCD, 32t, steel Traverse SL 29
REAR SHOCK	Fox Float DPS Factory, Kashima, 3- position adjustment, 52.5x210mm, Kashima coating, Rx Trail Tune
BATTERY	Specialized M3-700, integrated battery 700Wh
CHARGER	Custom charger, 42V4A w/ Rosenberger plug
WIRING HARNESS	Custom Specialized harness